

EATON

Powerware

**Powerware 5115
Uninterruptible Power
System**

**500-1400 VA advanced power
protection for office servers**



Features

- ~ High performance protection ~
Software Suite bundled
- ~ ABM™, prolongs battery life by 50%
- ~ Hot-swappable user replaceable batteries
- ~ Australian output sockets eliminate messy adaptors ~
Standard USB and RS232 serial ports extend
communication capacity

Options

- ~ ConnectUPS-E external Web/SNMP adaptor

Typical Applications

- ~ Small office servers
- ~ High-capacity PCs and workstations

Product Snapshot

Power Rating:	500-1400 VA
Voltage:	240 VAC
Frequency:	50 Hz
Configuration:	Plug-and-play Tower
Topology:	Line-interactive

Designed to offer advanced power protection for office servers and other critical applications, Powerware 5115 protects your equipment against five of the nine most common power problems that can harm your equipment or result in corrupted data.

In offices a crucial part of the work is stored on servers and reliable shutdown software is needed to ensure that no data is lost even during longer power outages. With Powerware 5115 and LanSafe III protecting the server, business goes on while the UPS invisibly and automatically takes care that no data is lost due to power problems. If a total outage threatens to exceed the system's backup time, LanSafe I II software automatically shuts down the

Technical Specifications

POWERWARE 5115				
Rating	500VA	750VA	1000VA	1400VA
Part number	51150500A	51150750A	51151000A	51151400A
Capacity (VA/Watts)	500/320	750/500	1000/670	1400/950
Dimensions WxDxH (mm)	150x268x185	150x333x185	150x333x185	150x388x185
Weight (kg)	8	12	13	17
Input connection	IEC320/10A	IEC320/10A	IEC320/10A	IEC320/10A
Output connection	3 x Aust. 10A	3 x Aust. 10A	3 x Aust. 10A	3 x Aust. 10A
Typical runtime (Full load)	5 min	6 min	5 min	5 min
Operational				
Nominal input voltage (Vac)	240 Vac			
Input voltage range	192 - 288 VAC (+/-20%)			
Operating frequency	50/60 Hz auto sensing			
Input power factor	Same as load			
Output voltage	240 Vac			
Output voltage regulation	216-254 VAC (-10%/+6%) or +/-5% on battery			
Overload capacity	110% 3 min; 150% 10 cycles			
Efficiency	95%			
User interface				
LED	Four LEDs; UPS on, UPS on battery, overload, alarm			
Standard communication ports	1 x RS232 & 1 x USB Port			
Optional	External SNMP adaptor			
Environmental				
Operating temperature	0 [°] C to +40 [°] C			
Storage temperature	-15 [°] C to +55 [°] C			
Altitude	< 3000 m			
Audible noise at 1 metre	< 40dB			
Certification				
Markings	CE/GS/UL/C-Tick			
Safety	EN 50091-1-1 & IEC 609050			
EMC (Class B)	AS62040.2.2001, C-Tick			
Battery Runtimes in minutes				
Load	51150500A	51150750A	51151000A	51151400A
200VA/128W	17	38	41	58
300VA/192W	11	27	28	41
500VA/320W	5	14	15	28
600VA/402W	-	9	10	19
750VA/503 W	-	6	8	14
900VA/603 W	-	-	6	10
1000VA/670W	-	-	5	8
1200VA/804W	-	-	-	6
1440VA/938W	-	-	-	5

This guide provides typical application information. Battery run times are approximate and may vary with equipment, configuration, battery age, temperature, etc.



Powerware and ABM are trade names, trademarks and/or service marks of Eaton Power Quality Corporation or its subsidiaries and affiliates. All other trademarks are property of their respective owners.



Ph: 61-8-9337 3711

Info@lightningman.com.au

Fax: 61-8-9337 3811

Unit 11, 5 Flindell Street, O'Connor, WA, 6163