


Power Line Filter – PLFA2RJ11



- 20 kA 8/20 μ s surge rating provides robust surge protection
- Three modes of protection: L-N, L-PE and N-PE
- LED status indication flag for status monitoring
- Includes mounting flange for direct mounting against wall



Part Number	PLFA2RJ11
Type	Australian Outlet
Nominal System Voltage (Un)	220 - 240 V
Max Continuous Operating Voltage (Uc)	275 V
Max Discharge Current (Imax)	20 kA 8/20 μ s L-N 20 kA 8/20 μ s L-PE 20 kA 8/20 μ s N-PE
Aggregate Surge Rating	60 kA 8/20 μ s
Max Discharge Current (Imax), L+L-PE	20 kA 8/20 μ s
Voltage Protection Rating (VPR)	600.0 V @ 3 kA
Leakage Current @ Un	0.2 mA Max
Frequency	50 - 60 Hz
Protection Modes	All modes protected
Material	Aluminum
Filtering	-3 dB @ 8 kHz
Status Indication	LED
Temperature	-25 to 70 °C
Depth (D)	252 mm
Height (H)	72 mm
Width (W)	100 mm
Unit Weight	1.5 kg
Complies With	ANSI®/IEEE® C62.41.2-2002 Cat A, Cat B, Cat C

Part Number	PLFA2RJ11
Certifications	C-Tick
Standard Packaging Quantity	1 pc
UPC	78285647550

Max Discharge Current (Imax), L+L-PE indicates RJ11 socket protection.

ANSI is a registered trademark of American National Standards Institute. IEEE is a registered trademark of The Institute of Electrical and Electronics Engineers, Inc.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2018 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.